

Halogen Display Light



A

- A. DLHA200
- Black
- Shown with DC275 clamp bracket (E)
- Arm length: 18" (46 cm)
- Head L 5.25" (13.3cm) x D 3.5" (8.9cm) x H 1.5" (3.8cm)
- Head and base made of high temperature plastic
- On/off switch at base of arm
- c/w 12' (366 cm) black cord with grounded plug
- Bulb: max. 200W 120 Volt halogen (DL200Q3 - included)



B

- B. DISP150
- Black
- 18" (46 cm) arm length
- 12' (366cm) SVT black cord with grounded plug
- On/off switch at base of arm
- Bulb: max. 150W 120 Volt (not included)

Incandescent Display Lights



C

D

- C. DISP150-75
- Black
- Same as DISP150 (B) with metal cover shade included
- Bulb: max. 75W 120 Volt (not included)
- D. DISP150-150
- Black
- Same as DISP150 (B) with metal cover shade included
- Bulb: max. 150W 120 Volt (not included)

All the lamps above slide into the brackets below



E



F



G



H

- G. DC360
- Aluminum
- Bracket designed to fit into pole of roll-up displays
- Stem OD 0.360" (9mm)

- E. DC275
- Black
- Clamp bracket
- Max. opening: 2.75" (7 cm)

- F. DB300
- Aluminum bar 3" (.76 cm) long to be screwed to top of panel or wall. (screws not supplied)
- Custom lengths available upon request

- H. DC480
- Aluminum
- Bracket designed to fit into pole of roll-up displays
- Stem OD 0.480" (12mm)